## AMENDMENT TO THE CLAIMS:

This listing of claims will replace all prior versions and listings of claims in the application:

## **Listing Of Claims:**

- Claim 1. (Currently Amended): A rubber mixture comprising
  - a) <u>at least</u> one <u>carboxylated hydrogenated nitrile rubbers and optionally er</u>

    mere <u>a carboxylated</u> nitrile <u>rubbererubber</u>
  - b) from 10 to 120 phr of one or more metal salts of an acrylate
  - c) from 5 to 80 phr of one or more liquid acrylates optionally applied onto a support,
  - d) from 0.01 to 8 phr of one or more silanes, and
  - e) optionally further additives and/or fillers.
- Claim 2. (Currently Amended): A rubber mixture according to Claim 1, wherein said carboxylated nitrile rubber(s) is selected from the group consisting of <a href="https://hydrogenated.NBR">hydrogenated.NBR</a>, carboxylated NBR, partially hydrogenated carboxylated NBR and completely hydrogenated carboxylated NBR-or mixtures of two or more of the members of the group.
- Claim 3. (Original): A rubber mixture according to Claim 1, wherein the metal salt of the acrylate is a Zn diacrylate or a Zn dimethacrylate or a mixture thereof.
- Claim 4. (Original): A rubber mixture according to Claim 1, wherein the liquid acrylate is butanediol dimethacrylate or trimethylolpropane trimethacrylate or a mixture thereof.
- Claim 5. (Original): A rubber mixture according to Claim 1, wherein vinylsilane is used as the silane.
- Claim 6. (Original): A rubber mixture according to Claim 1, wherein said mixture further more contains a silicate filler, carbon black, zinc oxide, magnesium oxide or a mixture of two or more of these components.

Mo-6608

- Claim 7. (Original): A rubber mixture according to Claim 1, wherein the mixture contains vulcanization retarders and/or vulcanization accelerators.
- Claim 8. (Currently Amended): A vulcanizable rubber mixture comprising a rubber mixture, which comprises
  - a) at least one carboxylated hydrogenated nitrile rubbers and optionally or more a carboxylated nitrile rubbers rubber
  - b) from 10 to 120 phr of one or more metal salts of an acrylate
  - from 5 to 80 phr of one or more liquid acrylates optionally applied onto a support,
  - d) from 0.01 to 8 phr of one or more silanes, and
  - e) optionally further additives and/or fillers.

## Claims 9 and 10. (Cancelled)

- Claim 11. (Currently Amended): A molding comprising a rubber mixture, which comprises
  - at least one carboxylated hydrogenated nitrile rubbers and optionally of more a carboxylated nitrile rubbers rubber.
  - b) from 10 to 120 phr of one or more metal salts of an acrylate
  - from 5 to 80 phr of one or more liquid acrylates optionally applied onto a support,
  - d) from 0.01 to 8 phr of one or more silanes, and
  - e) optionally further additives and/or fillers.

## Claim 12. (Cancelled)